

**External bypass system allows more water into the system to protect from heat build-up**



**Three (3) year warranty on all Subaru engines**

**Ten (10) year limited warranty on pump**

**Water filter with clear sleeve for screen inspection**



**Powder coated 1 1/4 inch steel tube handles, gun/wand holder for convenient storage**



CW-3004-4MGH

**1/4 inch powder coated steel base plate**



**Heavy-duty dual cogged belt drive system to**



**Pneumatic mag tires with tubes for longer life and solid steel threaded axle**



Model #	CW-2505-4MGH	CW-2505-4MGV	CW-3004-4MGH	CW-3004-4MGV	CW-3255-4MVO*	CW-3504-4MGH	CW-3504-4MGR
Pressure (psi)	2500	2500	3000	3000	3200	3500	3500
Flow (gpm)	4.4	4.4	3.5	3.5	4.9	3.7	3.7
Engine	Honda OHV	Vanguard OHV	Honda OHV	Vanguard OHV	Vanguard OHV	Honda OHV	Subaru OHC
Horsepower	11.0	11.0	11.0	11.0	16.0	13.0	13.5
Dim. (LxWxH)	45.5in.x28in.x26in.	45.5in.x28in.x26in.	45.5in.x28in.x26in.	45.5in.x28in.x26in.	46in.x28in.x30in.	46in.x28in.x30in.	46in.x28in.x30in.
Shipping weight	289 lbs.	295 lbs.	284 lbs.	284 lbs.	328 lbs.	291 lbs.	291 lbs.
Net weight	215 lbs.	221 lbs.	213 lbs.	220 lbs.	250 lbs.	216 lbs.	216 lbs.

Model #	CW-3504-4MGV	CW-4003-3MGH	CW-4003-3MGR	CW-4003-3MGV	CW-4004-3MVO*	CW-4004-4MVO*^
Pressure (psi)	3500	4000	4000	4000	4000	4000
Flow (gpm)	3.7	3.0	3.0	3.0	4.0	4.0
Engine	Vanguard OHV	Honda OHV	Subaru OHC	Vanguard OHV	Vanguard OHV	Vanguard OHV
Horsepower	13.0	13.0	13.5	13.0	16.0	16.0
Dim. (LxWxH)	46in.x28in.x30in.	46in.x28in.x30in.	46in.x28in.x30in.	46in.x28in.x30in.	46in.x28in.x30in.	46in.x28in.x30in.
Shipping weight	293 lbs.	291 lbs.	291 lbs.	293 lbs.	327 lbs.	327 lbs.
Net weight	218 lbs.	216 lbs.	216 lbs.	218 lbs.	249 lbs.	249 lbs.

\*Electric start (battery included).

^Model equipped with AR pump, all other models equipped with General pumps.



CW-3504-4MGR

**Additional Features**

- Performance-proven engine with low-oil protection
- Belt drive triplex piston General or AR pump with ceramic plungers
- Thermal relief valve
- Stainless-steel and brass unloader mounted on base plate
- Forged brass manifold (nickel plated brass on CW-4004-3MVO)
- Two-piece belt guard with 1/4-turn release for quick access to belts
- Convenient hose wrap
- Dual rubber isolators
- Quick connect nozzles (0°, 15°, 25° and 40°)
- 3/8 inch x 50 foot non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36 inch lance with rubber grip

**Options:**

- CX-0005 **Insulated dual lance** - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips
- CX-0006 **4000 PSI hose** - Upgrades pressure hose to 4000 PSI rating
- CX-0027, CX-0045 **Electric start (battery included)** - For easy starting
- CX-0050, CX-0051 **Electric start (battery included)** - For easy starting
- CX-0054, CX-0055 **Roll cage** - Designed for cold water pressure washers to protect equipment, comes with lifting hook, 1-1/4 inch powder coated steel tubing
- AW-8400-0021 **Low pressure detergent injection** - Allows the user to apply the recommended detergents
- 50-0161 **High pressure detergent injection** - High pressure water mixes with detergent to clean even the heaviest build-up
- TX-1302-M **Puncture-proof tires** - Tires are flat-free, maintenance-free and non-marking, 13 inch, white hub, two tires

Model #	CX-0005	CX-0006	CX-0027	CX-0045	CX-0050	CX-0051	CX-0054	CX-0055	AW-8400-0021	50-0161	TX-1302-M
CW-2505-4MGH	●	●	●				●		●	●	●
CW-2505-4MGV	●	●			●		●		●	●	●
CW-3004-4MGH	●	●	●				●		●	●	●
CW-3004-4MGV	●	●			●		●		●	●	●
CW-3255-4MVO	●								●	●	●
CW-3504-4MGH	●			●			●		●	●	●
CW-3504-4MGR	●						●		●	●	●
CW-3504-4MGV	●					●	●		●	●	●
CW-4003-3MGH	●			●			●		●	●	●
CW-4003-4MGR	●						●		●	●	●
CW-4003-3MGV	●					●	●		●	●	●
CW-4004-3MVO	●							●	●	●	●
CW-4004-4MVO	●							●	●	●	●

**2111 Catalina**  
**Pasadena, TX 77503**  
**281-479-5966 800-458-6304**  
**www.alklean.com**