

This versatile unit features an 8 hour run time and is perfect for continuous use applications.



CWC-5004-1MGH

Two (2) year limited parts & labor warranty

Seven (7) year limited warranty on pump

**Electric start (battery included)**



**Removable fuel tank (11.5 gallon capacity) allows for 8 hour running time**



**Powder coated steel frame with roll cage and lifting hook**



**Pneumatic mag tires with tubes, locking tire brake and solid steel threaded axles**



### Additional Features

- Performance-proven OHV engine with low-oil protection
- Belt drive triplex piston General or AR pump with ceramic plungers
- Thermal relief valve
- Preset stainless-steel and brass unloader
- Forged brass manifold
- Safety relief valve
- Water filter with clear sleeve for screen inspection
- Heavy-duty dual cogged belt drive system with cast iron pulleys
- Two-piece belt guard with 1/4-turn release for quick access to belts
- Hose wrap with gun/wand holder
- Low tone high mount muffler (5005 & 6004 models only)
- Quick connect nozzles (0°, 15°, 25° and 40°)
- 3/8 inch x 50 foot non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 48 inch lance with rubber grip (36 inch lance with rubber grip on CWC-4004-1MGV only)



Model #	CWC-4004-1MGV	CWC-4005-2MGH*	CWC-4005-1MGH
Pressure (psi)	4000	4000	4000
Flow (gpm)	4.0	5.0	5.0
Engine	Vanguard OHV	Honda OHV	Honda OHV
Horsepower	16.0	20.0	20.0
Dim. (LxWxH)	43in.x27.75in.x36in.	43in.x27.75in.x36in.	43in.x27.75in.x36in.
Shipping weight	481 lbs.	501 lbs.	501 lbs.
Net weight	358 lbs.	378 lbs.	378 lbs.

Model #	TX-1304-M
All Models	<input checked="" type="checkbox"/>

Model #	CWC-5004-2MGH*	CWC-5004-1MGH	CWC-5005-2MGH*	CWC-6004-2MGH*
Pressure (psi)	5000	5000	5000	6000
Flow (gpm)	4.0	4.0	4.5	3.7
Engine	Honda OHV	Honda OHV	Honda OHV	Honda OHV
Horsepower	20.0	20.0	24.0	24.0
Dim. (LxWxH)	43in.x27.75in.x36in.	43in.x27.75in.x36in.	43in.x27.75in.x36in.	43in.x27.75in.x36in.
Shipping weight	501 lbs.	501 lbs.	511 lbs.	511 lbs.
Net weight	378 lbs.	378 lbs.	388 lbs.	388 lbs.

\*Models equipped with General pumps, all other models equipped with AR pumps.

**Options:**  
TX-1304-M

Puncture-proof tires - Tires are flat-free, maintenance-free and non-marking, 13 inch, white hub, four tires

**2111 Catalina**  
**Pasadena, TX 77503**  
**281-479-5966 800-458-6304**  
**www.alklean.com**