

Hotsty

UNIVERSAL CLEANING SOLUTIONS



MODEL 555SS

Hot-Water Pressure Washer

The Model 555SS is a popular industrial-grade pressure washer in a compact, affordable package.

2.2 GPM @ 1300 PSI



■ **2 HP, 115V, 1PH electric motor** is drip proof and comes with thermal overload protection and manual reset.

■ **Convenient hose-reel bracket** accepts swivel or stationary reels for ease in hose maneuverability and storage.

■ **Adjustable upstream detergent injection** ensures high-pressure sudsing for better cleaning.

■ **Rust-proof, non-contaminating polyethylene fuel tank** includes easy-access sediment drain and fuel gauge in cap.



■ **Hotsty duplex, direct-drive, positive-displacement pump** carries seven-year crankcase and lifetime manifold warranties.

■ **Hose reel (optional)** makes hose mobility and storage easy and convenient. Also keeps work areas neat and safe while protecting hoses from damage.

■ **Pressure-relief valve** protects the machine and user.

■ **Stainless-steel coil skin** provides extra durability to withstand the elements.

■ **50-ft. length of high-pressure hose** for easy maneuverability around a large cleaning area.

■ **Upright, oil-fired burner** delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil.



■ **Simple, easy-to-use control panel** includes adjustable temperature control plus heavy-duty heater and pump motor switches.

■ **Built-in wand holder** provides convenient storage.

■ **37-ft. power cord** with safety **Ground Fault Circuit Interrupter (GFCI breaker)**.

■ **Semi-pneumatic wheels** eliminate the risk of flats.

■ **Adjustable, spray-angle nozzle** with 0° to 80° spray patterns adjusts easily under high pressure.

Hotsy's Model 555SS is an all-purpose, heavy-duty cleaning machine!

From construction, manufacturing, trucking, agriculture, fast-food shops, food processing and automotive repair ...the Model 555SS is designed for just about every industry needing pressure cleaning. The Model 555SS delivers big cleaning punch in a compact, portable and affordable package.

Discover Hotsy's no-cost benefits

Choose the Model 555SS for its high performance and rugged dependability. Then enjoy the benefits of doing business with the leader in industrial cleaning equipment. You'll find more than 120 models of pressure washers to choose from, free on-site demos, factory-trained service people, pre-delivery dealer prep, on-site machine checkout, operator training, local parts and accessory inventory, and a quality warranty program.

Accessories to match your application

Hotsy's custom accessories tailor the Model 555SS pressure washer to fit your specific requirements, making your cleaning jobs faster, easier and better. Choose from extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, foam applicator, wet sandblaster, rotating brush and more.



Clean better with Hotsy detergents

Hotsy's broad selection of biodegradable detergents are formulated specifically for high-temperature, high-pressure cleaning. This means you get the best results from your Hotsy pressure washer, as well as protect it. Exclusive advanced-formula HCC additives continuously clean the lime and mineral buildup that can occur in your washer's coil and fittings. This cleaning action reduces replacement costs and improves machine performance. Most Hotsy detergents are USDA and Canadian Agriculture approved. And they're concentrated, so a little goes a long way.

Call today for a demo!

Find out for yourself why the Hotsy Model 555SS is right for your tough cleaning tasks. Call your Hotsy Distributor today for all the details and a FREE on-site demo.



21 Inverness Way East, Englewood, Colorado 80112-5796
Tel: (303) 792-5200 **1-800-525-1976** Fax: (303) 792-0547
e-mail: info@hotsy.com or visit our website: www.hotsy.com

P/N 768920D Printed in USA Effective 3/03 Supercedes 768920C (5/02) Specifications and product descriptions subject to change without notice. © 2003 Hotsy

America's #1 Manufacturer of Cleaning Systems



Model 555SS Specifications

2.2 GPM @ 1300 PSI; 2 HP, 115V, 1-phase electric motor; 20 Amp; oil-fired water heater; shipping weight: 352 lbs.

Water Pump Volume: 2.2 GPM (8.33 lpm); 132 GPH (499.8 lph).

Water Pump Pressure: 1300 PSI (89.66 bars).

Water Pump: Hotsy duplex, direct-drive, positive-displacement pump; ceramic plungers, brass manifold, oil-bath crankcase.

Pump Drive: 2 HP, 115V, 60 Hz, 1PH electric motor; 56 frame, open drip-proof with thermal overload protection and manual reset.

Water Heater: Oil fired, 197,000 BTU/hr., UL-listed burner; pressure-atomizing type with automatic electric ignition. Your choice of #1 or #2 diesel, kerosene or #1 home heating oil as fuel. Fuel filter standard. Color-coded fuel lines indicate direction of flow. 8-gallon, removable, rust-proof, non-contaminating, polyethylene fuel tank with tapered bottom and sediment drain. Fuel gauge in cap.

Heating Coil: Schedule 80, ASTM A53 close coiling pipe; hydrostatic pressure tested; vertically fired. Heating coil is sheathed in a full-length sheet-metal wrap. Equipped with an independently welded heat-retention baffle plate.

Stack Size: 8" diameter.

Controls: Adjustable temperature control; self-cleaning, safety pressure-relief valve; heavy-duty rocker type ON/OFF pump motor and water-heater switches; upstream detergent injector.

Wand Assembly: Trigger-gun control with cool grip, quick-coupled to heavy-duty, chrome-plated wand with insulated grip.

Nozzle: Adjustable, spray-angle nozzle with 0° to 80° spray patterns. Adjusts easily even under high pressure.

Hose: 3/8" ID, 50 ft. wire braid with swivel fittings at both ends; 3000 PSI working pressure; burst pressure is at least 4 times working pressure; oil and chemical resistant.

Portability: Standard; heavy-duty, semi-pneumatic, Ace-Tuf®, ball-bearing wheels.

Optional Accessories: Extra hose lengths, hose reels (hose reel bracket standard), wand extensions, quick couplers, downstream detergent injector, wet sandblaster, rotating brush and foam applicator.

Construction: Durable, heavy-gauge sheet-metal chassis.

Finish: High-gloss, powder coat.

Dimensions: L-42" (106.68 cm), W-29" (73.66 cm), H-49" (124.46 cm).

Alklean Industries, Inc.

2111 Catalina

Pasadena, TX 77503

Ph 281-479-5966 or 1-800-458-6304

Fx 281-479-3890