



1800 Series

Hot Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

Choose from 12 Models

50-ft. length of high-pressure hose for easy cleaning in large areas

Upright Burner (558,000 BTUs) delivers high-temperature performance while maintaining a constant temperature

Stainless-steel coil skin provides extra durability to withstand the elements, resist corrosion and endure rough treatment

Thermal rupture disk protects machine and user from thermal expansion

10 HP Baldor electric motor available in 208V, 230V, 460V and 575V, 1PH and 3PH

Simple easy-to-use control panel includes adjustable temperature control with precision safety controls

Quick disconnect stainless steel nozzles are color coded for quick and easy changing between 0°, 15° and 40° spray nozzles

Elevated gas valve

Float tank maintains constant pressure and flow while preventing sediment from entering the machine's components

Built-in wand holder provides convenient storage



Equipped with these standard features:

- Electronic ignition
- Hour meter
- Safety thermal shutdown
- Float tank
- Time delay shut down

FEATURES

- Natural Gas or optional LP-Fired
- 4.7 to 5.9 GPM @ 2500 to 3000 PSI
- 208V-230V, 1PH; 208V 230V, 460V or 575V, 3PH
- Efficient 558,000 BTU



Hotsy Triplex positive-displacement pump carries 7-year warranty



Heater coil carries a 5-year warranty

www.Hotsy.com

Nothing Cleans Like a Hotsy!

1800 SERIES Hot Water Pressure Washers

■ Natural Gas or optional LP-Fired ■ 4.7 to 5.9 GPM @ 2500 to 3000 PSI ■ 208V-230V, 1PH; 208V 230V, 460V or 575V, 3PH ■ 558,000 BTU

Designed for tough, industrial cleaning.

SPECIFICATIONS

BELT DRIVE

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	PUMP	DRIVE	HOSE	SHIP WT (lbs)
1812SS	5.9	2500	10	1030	230/1	42	NG	Hotsy Triplex	Belt	50'	855
1812SS-208	5.9	2500	10	1030	208/1	48	NG	Hotsy Triplex	Belt	50'	860
1822SS	5.9	2500	10	1030	230/3	28	NG	Hotsy Triplex	Belt	50'	870
1822SS-208	5.9	2500	10	1030	208/3	33	NG	Hotsy Triplex	Belt	50'	870
1825SS	5.9	2500	10	1030	460/3	14	NG	Hotsy Triplex	Belt	50'	830
1836SS	5.9	2500	10	1030	575/3	11	NG	Hotsy Triplex	Belt	50'	850
1852SS	4.7	3000	10	851	230/1	42	NG	Hotsy Triplex	Belt	50'	865
1852SS-208	4.7	3000	10	851	208/1	48	NG	Hotsy Triplex	Belt	50'	870
1855SS	4.7	3000	10	851	460/3	14	NG	Hotsy Triplex	Belt	50'	870
1856SS	4.7	3000	10	851	575/3	11	NG	Hotsy Triplex	Belt	50'	845
1862SS	4.7	3000	10	851	230/3	28	NG	Hotsy Triplex	Belt	50'	880
1862SS-208	4.7	3000	10	851	208/3	33	NG	Hotsy Triplex	Belt	50'	845

Dimensions: 51.5"l x 25.6"w x 55.25"h



Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all 40 Hotsy detergent formulations contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Spend some time with a Hotsy Expert

Hotsy has more than 130 local Sales & Service Distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.



OPTIONS for 1800 SERIES

- **Primary Remote Station** (1st Remote)
- **Additional Remote Station** (Field installed)
- **Auto Start/Stop** (Factory installed)
- **Remote Soap Option** (Field installed)
- **LP Conversion Kit** (Factory installed)
- **10" Draft Diverter** (Field installed)

Hotsy Accessories customize your application for top performance



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe



High-pressure turbo nozzles for faster cleaning

Telescoping wands extend to 24' to reach high places without scaffolding



Heavy-duty, high-pressure hoses in lengths up to 150-ft.



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping

hotsy *Nothing Cleans Like a Hotsy!*

Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 97-0350 Effective 5/06 Specifications & product descriptions subject to change without notice. ©2006 Hotsy



NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.

Distributed by:

Alklean Industriest, Inc.
 2111 Catalina Drive
 Pasadena, Texas 77503
 281-479-5966 281-479-3890 (fax)
 www.alklean.com