



5700 Series

Hot-Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

Electric / Belt Drive

Upright burner delivers high efficiency and maintains constant temperature using oil or natural gas

Thermal rupture disk protects the machine and user from heat expansion

Thermal shutdown protects pump from overheating

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning



Heater coils carry a 5-year warranty

15HP Baldor 208V, 230V or 460V, 3PH electric motor is drip proof and comes with thermal overload protection

Float tank helps maintain constant pressure and flow and helps prevent sediment from entering the machine's components. A great feature for use in well-water environments and low-water situations

Insulated Hotsy Trigger Gun and Insulated wand with ergonomic, adjustable side handle

Shutdown Timer automatically turns off machine when not in operation for preset time

Simple, easy-to-use control panel includes adjustable temperature control with precision safety controls

Water-resistant cabinet, electrical box and motor



Model S5732-5 natural gas-fired

50-ft. length of high-pressure hose for ease in cleaning around a large area

Quick disconnect stainless-steel nozzles are color-coded for quick and easy changing between 0°, 15°, 40° spray nozzles



Hotsy triplex, positive-displacement pump carries seven-year warranty

Every Hotsy comes with over 37 years of experience and rugged durability built-in

FEATURES

- 7.8 GPM @ 3000 PSI
- Oil-Fired or Natural Gas-Fired Burner
- 208V, 230V or 460V, 3PH 15HP Baldor Motors
- ETL-Certified to UL-1776 safety standards

www.Hotsy.com

Nothing Cleans Like a Hotsy!

5700 SERIES Hot-Water ELECTRIC Pressure Washers

- Oil-Fired or Natural Gas-Fired
- 7.8 GPM @ 3000 PSI
- Hotsy Triplex Pump with 7-yr warranty
- ETL-Certified for safety

Designed for tough, industrial cleaning.

SPECIFICATIONS											BELT DRIVE	
MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	BTU/HR	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
S5730-3	7.8	3000	15	230/3	47	Oil	768,000	Hotsy Triplex	Belt	Optional	50'	1060
S5733-1	7.8	3000	15	460/3	25	Oil	768,000	Hotsy Triplex	Belt	Optional	50'	1070
S5730-5	7.8	3000	15	208/3	50	Oil	768,000	Hotsy Triplex	Belt	Optional	50'	1060
S5732-5	7.8	3000	15	208/3	47	NG	720,450	Hotsy Triplex	Belt	N/A	50'	985
S5732-4	7.8	3000	15	230/3	45	NG	720,450	Hotsy Triplex	Belt	N/A	50'	985
S5735-3	7.8	3000	15	460/3	23	NG	720,450	Hotsy Triplex	Belt	N/A	50'	975

Dimensions: 59"l x 32.5"w x 50.5"h



Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all 40 Hotsy detergent formulations contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Spend some time with a Hotsy Expert

Hotsy has more than 130 local Sales & Service Dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Rely on your network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.



OPTIONS for 5700 SERIES

- **Primary & Additional Remote Stations** provide easy operation in wash bays or multiple stations
- **Remote Soap Option** controls soap application from remote station (requires remote station)
- **Auto Start/Stop** provides preset & adjustable on/off machine operation
- **10" Natural Gas-Fired Draft Diverter** prevent backdrafts; keeps cold air out & prevents water from running down vent pipes

Hotsy Accessories customize your application for top performance



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe



High-pressure turbo nozzles for faster cleaning

Telescoping wands extend to 24' to reach high places without scaffolding



Heavy-duty, high-pressure hoses in lengths up to 150-ft.



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping



Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 8.914-183.0 Effective 7/07 Specifications & product descriptions subject to change without notice. ©2007 Hotsy



NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.

Distributed by:

Alklean Industries, Inc.
 2111 Catalina Drive
 Pasadena, Texas 77503
 281-479-5966
 281-479-3890 (fax)
 www.alklean.com