



{ Stationary - Skid-Mount }

# HDS Series

## Gasoline/Diesel- Belt Drive

Designed with professional contract cleaners in mind, the HDS Series is perfect for the heaviest construction applications, and durable enough to handle 24-hours-a-day, seven-days-a-week run-time.




HDS-3505-OH6G



### Additional Features:

- ✓ Performance-proven OHV engine with low-oil protection or liquid-cooled Kubota diesel engine (battery included on Kubota engines)
- ✓ Electric start (battery not included on gasoline models)
- ✓ Belt drive triplex ceramic plunger pump
- ✓ Hour meter\*
- ✓ Adjustable temperature control\*
- ✓ Adjustable high pressure detergent injection\*
- ✓ Polyethylene float tank
- ✓ Engine fuel tank
- ✓ Polyethylene burner fuel tank
- ✓ Racor fuel/water separator
- ✓ Diesel fired burner
- ✓ Horizontal schedule 80 pipe coil
- ✓ Pressure switch and thermal relief valve safety controls
- ✓ 471,800-BTU's per hour rating
- ✓ 10.0-gallon fuel tank capacity
- ✓ 10.0-gallon burner tank capacity with 3.37-gph burner fuel consumption
- ✓ Wrinkle-finish powder coated steel, protective square tubing roll cage frame assembly
- ✓ Three (3) quick connect high pressure nozzles (0°, 15°, 40° for cold/hot water operation, low pressure nozzle)
- ✓ 25-degree nozzle for wet steam operation\*
  - 2000-PSI @ 250°F (HDS-3005, 3006, 3505 & 3506 models)
  - 4000-PSI @ 250°F (HDS-4005 models)
- ✓ 50-foot x 3/8-inch high pressure hose with quick connects
- ✓ Professional-grade insulated trigger gun with safety lock-off
- ✓ Adjustable pressure insulated dual lance



Three-way ball valve for inlet water selection\*

120V/15-amp auxiliary duplex GFCI outlet\*

Stainless-steel coil wrap and control panel\*

Stainless-steel removable front panel for access to pump

2600-watt generator

*\*These features are, in part, what puts Mi-T-M a cut above the competition!*

**Specifications:**

<b>Model #</b>	<b>HDS-3005-0K6G<sup>^</sup></b>	<b>HDS-3005-0V6G<sup>^</sup></b>	<b>HDS-3006-0B7G<sup>*</sup></b>	<b>HDS-3505-0H6G<sup>^</sup></b>	<b>HDS-3505-0K6G<sup>^</sup></b>	<b>HDS-3505-0V6G<sup>^</sup></b>	<b>HDS-3505-0B7G<sup>*</sup></b>
<b>Pressure (psi)</b>	3000	3000	3000	3500	3500	3500	3500
<b>Flow (gpm)</b>	4.8	4.8	5.6	4.7	4.7	4.7	4.7
<b>Engine</b>	Kohler	Vanguard OHV	Kubota	Honda OHV	Kohler	Vanguard OHV	Kubota
<b>Horsepower</b>	18.0	16.0	15.5	20.0	20.0	21.0	15.5
<b>Dim. (LxWxH)</b>	50in.x34in.x45in.	50in.x34in.x45in.	56.5in.x34in.x45in.	50in.x34in.x45in.	50in.x34in.x45in.	50in.x34in.x45in.	56.5in.x34in.x45in.
<b>Shipping weight</b>	854 lbs.	854 lbs.	940 lbs.	854 lbs.	854 lbs.	854 lbs.	940 lbs.
<b>Net weight</b>	750 lbs.	750 lbs.	836 lbs.	750 lbs.	750 lbs.	750 lbs.	836 lbs.

<b>Model #</b>	<b>HDS-3506-0H6G<sup>^</sup></b>	<b>HDS-3506-0K6G<sup>^</sup></b>	<b>HDS-4005-0B7G<sup>*</sup></b>	<b>HDS-4005-1H6G<sup>^</sup></b>	<b>HDS-4005-1K6G<sup>^</sup></b>
<b>Pressure (psi)</b>	3500	3500	4000	4000	4000
<b>Flow (gpm)</b>	5.6	5.6	4.5	5.0	5.0
<b>Engine</b>	Honda OHV	Kohler	Kubota	Honda OHV	Kohler
<b>Horsepower</b>	24.0	25.0	15.5	24.0	25.0
<b>Dim. (LxWxH)</b>	50in.x34in.x45in.	50in.x34in.x45in.	56.5in.x34in.x45in.	50in.x34in.x45in.	50in.x34in.x45in.
<b>Shipping weight</b>	854 lbs.	854 lbs.	940 lbs.	854 lbs.	854 lbs.
<b>Net weight</b>	750 lbs.	750 lbs.	836 lbs.	750 lbs.	750 lbs.

*<sup>\*</sup>Diesel unit.  
<sup>^</sup>Note: AR Pumps are available on these models "0\_6A" or "0\_7A".*



HDS-4005-0B7G

**2111 Catalina  
 Pasadena, TX 77503  
 281-479-5966 800-458-6304  
 www.alklean.com**

**Options:**

- 50-0170 Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port
- 850-0324 Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing
- AW-5740-0000 Wheel kit - Allows unit to become portable
- HX-0100, HX-0102 300°F steam upgrade - Steam option lowers unit pressure to 350-PSI, 240°F rise over ambient with a maximum of 300°F
- HX-0144 Dual gun - Two guns may be sprayed at the same time; flow is divided between the two guns while each operator maintains equal system pressure
- HX-0147 Four (4) point lifting capability - Allows unit to be lifted by crane
- HX-0150 - HX-0152 Trapping unloader - For longer hose runs and cleaning elevated areas
- HX-0155 Trapping unloader - For longer hose runs and cleaning elevated areas

Model #	50-0170	850-0324	AW-5740-0000	HX-0100	HX-0102	HX-0144	HX-0147	HX-0150	HX-0151	HX-0152	HX-0155
HDS-3005	●	●	●	●			●	●			
HDS-3006	●	●	●		●	●	●				●
HDS-3505	●	●	●	●			●		●		
HDS-3506	●	●	●		●	●	●			●	
HDS-4005	●	●	●				●				