

HHS Specifications

Model No.	PSI	GPM	HP/Motor	Plug Type	Burner Fuel Tank Cap.	Consumption	BTU	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-1002-1E1G	1000	2.0	1.5/120V, 10, 16.2A	NEMA 5-20P	10.0 gallon	1.23 gph	172,000	57in.x30in.x41.5in.	606 lbs.	486 lbs.
HHS-1003-1E1G	1000	2.8	2.0/120V, 10, 20.0A	NEMA 5-20P	10.0 gallon	1.84 gph	257,000	57in.x30in.x41.5in.	610 lbs.	490 lbs.
HHS-1502-1E1G	1500	1.8	2.0/115V, 10, 19.9A	NEMA 5-20P	10.0 gallon	2.23 gph	172,000	57in.x30in.x41.5in.	610 lbs.	490 lbs.

Model No.	PSI	GPM	HP/Motor	Plug Type	Burner Fuel Tank Cap.	Consumption	BTU	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-2004-1E2G	2000	4.2	6.0/230V, 10, 28.0A	NEMA 6-30P	10.0 gallon	2.76 gph	386,400	57in.x30in.x41.5in.	670 lbs.	550 lbs.
HHS-2004-1E3G	2000	4.2	6.0/230V, 30, 18.5A	NEMA L15-20P	10.0 gallon	2.76 gph	386,400	57in.x30in.x41.5in.	670 lbs.	550 lbs.
HHS-2004-1E4G	2000	4.2	6.0/460V, 30, 12.0A	NEMA L16-20P	10.0 gallon	2.76 gph	386,400	57in.x30in.x41.5in.	670 lbs.	550 lbs.
HHS-2004-1E8G	2000	4.2	6.0/208V, 10, 30.7A	NEMA 6-50P	10.0 gallon	2.76 gph	386,400	57in.x30in.x41.5in.	670 lbs.	550 lbs.
HHS-2004-1E9G	2000	4.2	6.0/208V, 30, 29.9A	NEMA L15-30P	10.0 gallon	2.76 gph	386,400	57in.x30in.x41.5in.	670 lbs.	550 lbs.

Model No.	PSI	GPM	HP/Motor	Plug Type	Burner Fuel Tank Cap.	Consumption	BTU	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-3004-1E2G	3000	3.9	8.0/230V, 10, 39.5A	NEMA 6-50P	10.0 gallon	2.14 gph	341,800	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E3G	3000	3.9	8.0/230V, 30, 22.5A	NEMA L15-30P	10.0 gallon	2.14 gph	341,800	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E4G	3000	3.9	8.0/460V, 30, 14.0A	NEMA L16-20P	10.0 gallon	2.14 gph	341,800	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E5G	3000	3.9	8.0/575V, 30, 12.0A	NEMA L17-30P	10.0 gallon	2.14 gph	341,800	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E8G	3000	3.9	8.0/208V, 10, 43.0A	NEMA 6-50P	10.0 gallon	2.14 gph	341,800	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E9G	3000	3.9	8.0/208V, 30, 25.5A	NEMA L15-30P	10.0 gallon	2.14 gph	341,800	57in.x30in.x41.5in.	700 lbs.	580 lbs.

Model No.	PSI	GPM	HP/Motor	Plug Type	Burner Fuel Tank Cap.	Consumption	BTU	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-3005-1E2G	3000	4.8	10.0/230V, 10, 46.5A	NEMA 6-50P	10.0 gallon	3.06 gph	428,400	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E3G	3000	4.8	10.0/230V, 30, 27.5A	NEMA L15-30P	10.0 gallon	3.06 gph	428,400	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E4G	3000	4.8	10.0/460V, 30, 16.5A	NEMA L16-20P	10.0 gallon	3.06 gph	428,400	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E5G	3000	4.8	10.0/575V, 30, 14.0A	NEMA L17-30P	10.0 gallon	3.06 gph	428,400	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E8G	3000	4.8	10.0/208V, 10, 50.7A	NEMA 6-50P	10.0 gallon	3.06 gph	428,400	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E9G	3000	4.8	10.0/208V, 30, 31.5A	NEMA L15-50P	10.0 gallon	3.06 gph	428,400	57in.x30in.x41.5in.	704 lbs.	584 lbs.

HHS-303-1E1A^A 300 2.5 1.5/120V, 10, 12.5A GFCI 15 Amp 10.0 gallon 57in.x30in.x41.5in. 480 lbs. 460 lbs.

^ASteamer unit Note: AR pumps are available on all models

Options

- 50-0170 Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port
- 850-0324 Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing
- HX-0161 Hour meter - Displays number of hours unit has been in operation
- HX-0162 Stainless-steel bottom wrap - Covers powder coated paint bottom wrap to stainless-steel
- HX-0163 13-inch mag tires - Upgrade to mag tires from white rims and tires
- HX-0164 Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting
- HX-0165, HX-0167 Option ready kit - This option is required if adding time delay shut down or auto start/stop
- HX-0166 Auto start/stop - When trigger gun is released timer will turn unit off, when trigger gun is pulled unit will restart
- HX-0171 Skid feet - Stationary applications
- HX-0172 - HX-0176 & HX-0195 250° Steam - Increases outlet temperature to 250°F
- HX-0196 Skid frame/roll cage design - Stationary applications
- TX-1304-W Puncture-proof tires - Tires are flat-free, maintenance-free, 13-inch, white hub, four tires

Model #	50-0170	850-0324	HX-0161	HX-0162	HX-0163	HX-0164	HX-0165	HX-0166	HX-0167	HX-0171	HX-0172	HX-0173	HX-0174
HHS-1002	•	•	•	•	•	•	•	•	•	•	•	•	•
HHS-1003	•	•	•	•	•	•	•	•	•	•	•	•	•
HHS-1502	•	•	•	•	•	•	•	•	•	•	•	•	•
HHS-2004	•	•	•	•	•	•	•	•	•	•	•	•	•
HHS-3004	•	•	•	•	•	•	•	•	•	•	•	•	•
HHS-3005	•	•	•	•	•	•	•	•	•	•	•	•	•
HHS-303	•	•	•	•	•	•	•	•	•	•	•	•	•

Model #	HX-0176	HX-0195	HX-0196	TX-1304-W
HHS-1002	•	•	•	•
HHS-1003	•	•	•	•
HHS-1502	•	•	•	•
HHS-2004	•	•	•	•
HHS-3004	•	•	•	•
HHS-3005	•	•	•	•
HHS-303	•	•	•	•



GFCI 15-amp plug



NEMA 5-20P, 20-amp plug



NEMA 6-30P, 30-amp plug



NEMA L15-50P, 50-amp plug



NEMA L16-20P, 20-amp plug



NEMA L17-30P, 30-amp plug



NEMA 6-50P, 50-amp plug



NEMA L15-20P, 20-amp plug



NEMA L15-30P, 30-amp plug

Distributed by:



Hot Water Pressure Washers HHS Series



HHS Series


The HHS Series offers portability and reliability suitable for the most rugged applications.

ELECTRIC POWERED - OIL HEATED - BELT DRIVE

PORTABLE



Belt drive triplex General or AR plunger pump has the best warranty in the industry



Fuel/water separator ensures clean fuel supply to the burner



Optional stack adapter allows 8-inch flue pipe to be installed to vent machine exhaust



Locking rear wheel brake prevents unit from rolling

Additional Features:

- ✓ Open drip-proof electric motor with thermal overload protection
- ✓ Easy pump oil drain
- ✓ Thermal relief valve
- ✓ Pressure switch and high limit switch safety controls
- ✓ 300°F/149°C operating temperature (HHS-303 only)
- ✓ Wand holder
- ✓ Insulated trigger gun with safety lock-off
- ✓ Adjustable pressure-insulated dual lance/wand (except on HHS-303)
- ✓ Single lance with dual insulated grips; steam nozzle (HHS-303)
- ✓ 50-foot x 3/8-inch high pressure hose with quick connects (50-foot steam hose on HHS-303)
- ✓ Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F



HHS-3004-1E2G



HHS-2004-1E4G shown with skid frame (HX-0196) option

